

# Thermex Thermatron, LP

## High Frequency Heat Sealers

### Indexer



### Features:

- ✓ Five-roll modular design; heavy-duty roll stand equipped with easy to re-set alignment guides to ensure proper lateral web travel.
- ✓ Web relaxing dancer roller; full-width clamp to secure material on roll stand.
- ✓ Indexer width is 30 inches - maximum roll diameter is 16 inches.
- ✓ Indexer stroke is adjustable from 0 inches to 36 inches.
- ✓ Adjustments are facilitated by means of a hand wheel and are easily determined by steel rule indicator.
- ✓ Calibrated in increments of 1/16 of an inch.
- ✓ Indexer is equipped with a control box which enables the operator to control the press and the indexer in automatic mode, semi-automatic mode, as well as special jog control for use in setup and/or splicing and replenishment.
- ✓ Emergency STOP switch.

### Options:

- ✓ PLC control with Servo drive allows for instantaneous length changes at every cycle if desired.
- ✓ Available with stroke lengths up to 54 inches and widths up to 36 inches.
- ✓ Print recognition system.

### Applications:

- ✓ Card holders, sheet protectors, CD holders and other products that are made directly from rolled material.

**Thermex Thermatron, LP**  
"High Frequency at Its Best"

10501 Bunsen Way, Suite 102  
Louisville, Kentucky 40299  
Ph: 502-493-1299 Fax: 502-493-4013  
[Sales@thermex-thermatron.com](mailto:Sales@thermex-thermatron.com)

[www.thermex-thermatron.com](http://www.thermex-thermatron.com)